



Cap. μF	50VDC				100VDC				200VDC				500VDC			
	N Lead		CASE CODE	MAX DIM A	N Lead		CASE CODE	MAX DIM A	N Lead		CASE CODE	MAX DIM A	N Lead		CASE CODE	MAX DIM A
	+/- 5%	+/- 10%			+/- 5%	+/- 10%			+/- 5%	+/- 10%			+/- 5%	+/- 10%		
0.01													181	182	5	.120
0.012													183	184	5	.120
0.015													185	186	5	.240
0.018													187	188	5	.240
0.022								121	122	5	.120		189	190	5	.360
0.027								123	124	5	.240		191	192	5	.360
0.033								125	126	5	.240		193	194	5	.480
0.039								127	128	5	.240		195	196	5	.480
0.047					061	062	5	.240	129	130	5	.360	197	198	5	.650
0.056	001	002	5	.120	063	064	5	.240	131	132	5	.360	199	200	4	.360
0.068	003	004	5	.240	065	066	5	.240	133	134	5	.480	201	202	4	.360
0.082	005	006	5	.240	067	068	5	.240	135	136	5	.480	203	204	4	.480
0.1	007	008	5	.240	069	070	5	.360	137	138	5	.650	205	206	4	.480
0.12	009	010	5	.360	071	072	5	.360	139	140	4	.360	207	208	4	.650
0.15	011	012	5	.360	073	074	5	.480	141	142	4	.360	209	210	3	.240
0.18	013	014	5	.480	075	076	5	.480	143	144	4	.480	211	212	3	.240
0.22	015	016	5	.480	077	078	5	.650	145	146	4	.480	213	214	3	.360
0.27	017	018	5	.650	079	080	4	.360	147	148	4	.650	215	216	3	.360
0.33	019	020	4	.360	081	082	4	.480	149	150	3	.240	217	218	3	.480
0.39	021	022	4	.480	083	084	4	.480	151	152	3	.240	219	220	3	.650
0.47	023	024	4	.480	085	086	4	.650	153	154	3	.360	221	222	1	.360
0.56	025	026	4	.240	087	088	4	.650	155	156	3	.360	223	224	1	.480
0.68	027	028	3	.240	089	090	3	.240	157	158	3	.480	225	226	1	.480
0.82	029	030	3	.240	091	092	3	.360	159	160	3	.650	227	228	1	.650
1	031	032	3	.360	093	094	3	.360	161	162	3	.650	229	230	2	.480
1.2	033	034	3	.360	095	096	3	.480	163	164	1	.480	231	232	2	.650
1.5	035	036	3	.480	097	098	3	.480	165	166	1	.480	233	234	6	.360
1.8	037	038	3	.480	099	100	3	.650	167	168	1	.650	235	236	6	.480
2.2	039	040	3	.650	101	102	1	.480	169	170	2	.480	237	238	6	.650
2.7	041	042	1	.360	103	104	1	.480	171	172	2	.650				
3.3	043	044	1	.480	105	106	1	.650	173	174	6	.360				
3.9	045	046	1	.480	107	108	2	.480	175	176	6	.360				
4.7	047	048	1	.650	109	110	2	.650	177	178	6	.480				
5.6	049	050	2	.650	111	112	6	.360	179	180	6	.650				
6.8	051	052	6	.360	113	114	6	.650								
8.2	053	054	6	.360	115	116	6	.480								
10	055	056	6	.480	117	118	6	.650								
12	057	058	6	.480	119	120	6	.650								
15	059	060	6	.650				-								

Note: "N" lead configuration is standard.
 "J" or "L" lead configurations can be obtained by adding the letter as a suffix to the dash number