



Cap. uF	50VDC						100VDC						200VDC						500VDC					
	N Lead		J Lead		Case Code	MAX DIM A	N Lead		J Lead		Case Code	MAX DIM A	N Lead		J Lead		Case Code	MAX DIM A	N Lead		J Lead		Case Code	MAX DIM A
	+/- 10%	+/- 20%	+/- 10%	+/- 20%			+/- 10%	+/- 20%	+/- 10%	+/- 20%			+/- 10%	+/- 20%	+/- 10%	+/- 20%			+/- 10%	+/- 20%	+/- 10%	+/- 20%		
0.15																			173	174	421	422	5	.120
0.18																			175	176	423	424	5	.240
0.22																			177	178	425	426	5	.240
0.27																			179	180	427	428	5	.240
0.33																			181	182	429	430	5	.360
0.39																			183	184	431	432	5	.360
0.47													113	114	361	362	5	.240	185	186	433	434	5	.360
0.56													115	116	363	364	5	.240	187	188	435	436	5	.480
0.68							055	056	301	302	5	.120	117	118	365	366	5	.360	189	190	437	438	5	.650
0.82							057	058	303	304	5	.240	119	120	367	368	5	.360	231	232	439	440	4	.360
1.0	001	002	241	242	5	.120	059	060	305	306	5	.240	121	122	369	370	5	.480	191	192	441	442	4	.360
1.2	003	004	243	244	5	.120	061	062	307	308	5	.240	123	124	371	372	5	.480	193	194	443	444	4	.360
1.5	005	006	245	246	5	.240	063	064	309	310	5	.360	125	126	373	374	5	.650	195	196	445	446	4	.480
1.8	007	008	247	248	5	.240	065	066	311	312	5	.360	127	128	375	376	4	.360	197	198	447	448	4	.650
2.2	009	010	249	250	5	.240	067	068	313	314	5	.480	129	130	377	378	4	.360	233	234	449	450	3	.240
2.7	011	012	251	252	5	.360	069	070	315	316	5	.480	131	132	379	380	4	.480	199	200	451	452	3	.360
3.3	013	014	253	254	5	.360	071	072	317	318	5	.650	133	134	381	382	4	.480	201	202	453	454	3	.360
3.9	015	016	255	246	5	.480	073	074	319	320	4	.360	135	136	383	384	4	.650	203	204	455	456	3	.360
4.7	017	018	257	258	5	.480	075	076	321	322	4	.360	137	138	385	386	3	.240	205	206	457	458	3	.480
5.6	019	022	259	260	5	.560	077	078	323	324	4	.480	139	140	387	388	3	.240	207	208	459	460	3	.650
6.8	223	224	261	262	4	.360	079	080	325	326	4	.480	141	142	389	390	3	.360	235	236	461	462	1	.480
8.2	021	022	263	264	4	.360	081	082	327	328	4	.650	143	144	391	392	3	.360	209	210	463	464	1	.480
10	023	024	265	266	4	.480	229	230	329	330	3	.240	145	146	393	394	3	.480	211	212	465	466	1	.480
12	025	026	267	268	4	.480	083	084	331	332	3	.240	147	148	395	396	3	.650	213	214	467	468	1	.650
15	027	028	269	270	4	.650	085	086	333	334	3	.360	149	150	397	398	1	.360	237	238	469	470	2	.650
18	029	030	271	272	3	.240	087	088	335	336	3	.360	151	152	399	400	1	.480	215	216	471	472	2	.360
22	031	032	273	274	3	.360	089	090	337	338	3	.480	153	154	401	402	1	.650	239	240	473	474	6	.360
27	033	034	275	276	3	.360	091	092	339	340	3	.650	155	156	403	404	1	.650	217	218	475	476	6	.360
33	035	036	277	278	3	.360	093	094	341	342	1	.360	157	158	405	406	2	.480	219	220	477	478	6	.480
39	037	038	279	280	3	.480	095	096	343	344	1	.480	159	160	407	408	2	.650	221	222	479	480	6	.650
47	039	040	281	282	3	.650	097	098	345	346	1	.480	161	162	409	410	6	.240		-	-	-	-	-
56	225	226	283	284	1	.360	099	100	347	348	1	.650	163	164	411	412	6	.360		-	-	-	-	-
68	041	042	285	286	1	.480	101	102	349	350	2	.480	165	166	413	414	6	.360		-	-	-	-	-
82	043	044	287	288	1	.480	103	104	351	352	2	.650	167	168	415	416	6	.480		-	-	-	-	-
100	045	046	289	290	1	.650	105	106	353	354	6	.360	169	170	417	418	6	.650		-	-	-	-	-
120	227	228	291	292	2	.480	107	108	355	356	6	.360	171	172	419	420	6	.650		-	-	-	-	-
150	047	048	293	294	2	.650	109	110	357	358	6	.480								-	-	-	-	-
180	049	050	295	296	6	.480	111	112	359	360	6	.650								-	-	-	-	-
220	051	052	297	298	6	.480	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
270	053	054	299	300	6	.650	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	

**Note:** "N" lead configuration is standard.  
 "J" or "L" lead configurations can be obtained by adding the letter as a suffix to the dash number.